

### SPECIFICATION FEATURES

**Optical System:** Patented field adjustable Co-Centric™ optical system delivers even light distribution over a range of lighting applications. Outer reflector is CNC spun aluminum with a durable, 85% reflective, polyester powder-coated finish. The inner reflector is fluted, specular aluminum.

**Housing:** Heavy gauge, die-cast aluminum. Removable top splice-compartment with cast aluminum hook. 3/4" K.O.'s top and sides.

**Ballast:** Constant Wattage Autotransformer. Copper-wound with laminated steel core. High Power factor with 4K ignitor. 100% factory tested after assembly.

**Source:** Pulse Start Metal Halide, for Vertical, Open-Rated operation, with internal Quartz shroud around arc-tube, clear envelope.  
(Lamp ordered separately).

**Socket:** Mogul Exclusionary Base (EX39). Porcelain, with "pink" glaze. Nickel-plated brass screwshell. Open rated, requiring extended-pin open-rated lamp.

**Finish:** White polyester powder coat.

**Listing:** UL Listed, suitable for damp locations.



**Magnetic Ballast, Metal Reflector**

NOTE: Assembled and shipped by a U.L. certified supplier. Made in USA

### ORDERING INFORMATION

CHGM	①	②	③	④
Family	Wattage	Source	Voltage	Options

① **WATTAGE:** 150 = 150 Watts 350 = 350 Watts  
 200 = 200 Watts 400 = 400 Watts  
 250 = 250 Watts 450 = 450 Watts  
 320 = 320 Watts

② **SOURCE:** PSM = Pulse Start Metal Halide  
 CMH = Ceramic Metal Halide

③ **VOLTAGE:** MT = Multi-Tap (120, 208, 240, 277)  
 TT = Tri-Tap (120, 277, 347)  
 480 = 480 Volt  
 277 = 277 Volt Lag/Reactor ballast

Please quote the catalog number (Cat. No.) by specifying the appropriate options.

④ **OPTIONS:**

**Cord:**

CB3 = 3 ft. Black cord      CW3 = 3 ft. White cord  
 CB6 = 6 ft. Black cord      CW6 = 6 ft. White cord  
 CB8 = 8 ft. Black cord      CW8 = 8 ft. White cord

**Plugs (Twist-lok caps)**

P51 = (NEMA L5-15P)      P71 = (NEMA L7-15P)  
 P52 = (NEMA L5-20P)      P72 = (NEMA L7-20P)  
 P53 = (NEMA L6-30P)      P73 = (NEMA L7-30P)  
 P61 = (NEMA L6-15P)      P81 = (NEMA L8-15P)  
 P62 = (NEMA L6-20P)      P82 = (NEMA L8-20P)  
 P63 = (NEMA L6-30P)      P83 = (NEMA L8-30P)

•SF = Single Fuse (120, 277, 347 volt)    •DF = Double Fuse (208, 240, 480 volt)

•QRS = Quartz Restrike (wattage equal or less than HID)

•Bi-Level Dimming: Consult Factory

**ACCESSORIES:** all field-installed; please order separately

•SCK = Safety Cable Kit

STINGRAY ENERGY SYSTEMS, LLC  
 1550 Douglas Drive  
 Charleston, IL 61920  
 Telephone 888•577•8464  
 Fax 217-348-5391  
 Web: www.stingrayenergy.com

Project: \_\_\_\_\_ Date: \_\_\_\_\_

Type: \_\_\_\_\_ Email: \_\_\_\_\_

Prepared by: \_\_\_\_\_

Comments/Additional info: