

SPECIFICATION FEATURES

Optical System: Patented field adjustable multi-focal optical system adapts to a broad range of lighting applications. Reflectors are Injection Molded Prismatic Acrylic. Tool-less adjusting mechanism, includes adjustment scale to assist in accurate field-adjustment.

Housing: Heavy gauge, die-cast aluminum with heat-dissipation fins and integral splice-compartment. Cast Aluminum hook with safety clasp included.

Ballast: Magnetic High Reactance Autotransformer. Copper-wound with laminated steel core. High Power factor with 4K ignitor. 100% factory tested after assembly.

Source: Pulse Start Metal Halide, for Vertical, Open-Rated operation, with internal Quartz shroud around arc-tube, clear envelope standard. (Lamp ordered separately)

Socket: Mogul Exclusionary Base (EX39). Porcelain, with "pink" glaze. Nickel-plated brass screwshell. Open rated, requiring extended-pin open-rated lamp.

Finish: White polyester powder coat

Listing: UL Listed, suitable for damp locations, 40° C ambient



NOTE: Assembled and shipped by a U.L. certified supplier. Made in USA

ORDERING INFORMATION

	①	②	③	④
EXCM	575	PSM		
Family	Wattage	Source	Voltage	Options

① **WATTAGE:** 575 = 575 Watts

② **SOURCE:** PSM = Pulse Start Metal Halide

Please quote the catalog number (Cat. No.) by specifying the appropriate options (1 and 2) as shown below:

③ **Voltage:** MT = Multi-Tap (120, 208, 240, 277)
 TT = Tri-Tap (120, 277, 347)
 480 = 480 volt
 277 = 277 volt Lag/Reactor ballast

④ **Options: Cord:**
 CB3 = 3 ft. Black cord CW3 = 3 ft. White cord
 CB6 = 6 ft. Black cord CW6 = 6 ft. White cord
 CB8 = 8 ft. Black cord CW8 = 8 ft. White cord

Plugs (Twist-lok caps)
 P51 (NEMA L5-15P) P71 (NEMA L7-15P)
 P52 (NEMA L5-20P) P72 (NEMA L7-20P)
 P53 (NEMA L5-30P) P73 (NEMA L7-30P)
 P61 (NEMA L6-15P) P81 (NEMA L8-15P)
 P62 (NEMA L6-20P) P82 (NEMA L8-20P)
 P63 (NEMA L6-30P) P83 (NEMA L8-30P)

SF = Single Fuse (120, 277, 347 volt)
 DF = Double Fuse (208, 240, 480 volt)
 QRS = Quartz Restrike (wattage equal or less than HID)
 Bi-Level Dimming - Consult Factory

Accessories: all field-installed please order separately
 SCK = Safety Cable Kit

STINGRAY ENERGY SYSTEMS, LLC

1550 Douglas Drive
 Charleston, IL 61920

Telephone: (847) 656-3557

Facsimile : (217) 348-5391

Web site : www.stingrayenergy.com