

SPECIFICATION FEATURES

- Optical Control: Unique dual reflector configuration delivers IES Type V beam pattern. Dual reflectors deliver exceptional beam control.
- Outer reflector: Acrylic Prismatic
- Housing: Heavy gauge die-cast aluminum.
- Light Source: Induction lamp, generator and antenna units engineered for optimal temperatures for long life.
- Listing: CUL/UL

NOTE: Fixtures are assembled and shipped from a U.L. certified supplier.



NOTE: Assembled and shipped by a U.L. certified supplier. Made in USA

How to specify a catalog number

PGE PGP		IND		
Family	Wattage	Source	Voltage	Options

Please quote the catalog number (Cat. No.) by specifying the appropriate options.

The GLDR catalog number is composed of the available options (1 through 5) listed below.

- 1 WATTAGE:**
 - 85 = 85 Watts
 - 55 = 55 Watts
- 2 VOLTAGE:**
 - LV = 120 Volts AC
 - HV = 208-277 Volts AC
- 3 OPTIONS:**
 - CD = Cord
 - P = Plug
 - HB = Hanger Bracket

STINGRAY ENERGY SYSTEMS, LLC
 1550 Douglas Drive
 Charleston, IL 61920
 Telephone 888•577•8464
 Fax 217.348.5391
 Web: www.stingrayenergy.com

Project: _____ Date: _____
 Type: _____ Email: _____
 Prepared by: _____
 Comments/Additional info: